



OBEX™ TILE: LOOP

Entrance Flooring

Construction

Tufted, Multi-Level Loop

Tile Size

50 cm x 50 cm (19.7" x 19.7")

Yarn Type

ECONYL® Solution-Dyed Nylon and Solution-Dyed Nylon Monofilament

Dye Method

Solution Dyed

Tufted Face Weight

27.9 oz/yd² (946 g/m²)

Gauge

1/12

Stitches Per Inch

11.3

Tufts

135.6/in² (2,100/100 cm²)

Finished Pile Height

0.255" (6.48 mm)

Average Density (Finished)

5,740

Standard Backing

PVC-Free WellBAC® Comfort Cushion

Available with TractionBack®

Recycled Content by Total Weight

33.3% Pre-Consumer,
6.6% Post-Consumer

Embodied Carbon

8.89 (kg CO₂e)/m²

Nominal Total Thickness

0.391" (9.9 mm)

Nominal Total Weight

104.2 oz/yd² (3,533 g/m²)

Flammability (Radiant Panel

ASTM-E-648)

≥ 0.45 (Class I)

Smoke Density (NFPA-258-T or

ASTM-E-662)

≤ 450

Methenamine Pill Test (CPSC FF-1-70 or ASTM D 2859

Self-Extinguishing

Lightfastness (AATCC 16E)

≥ 4.0 at 80 Hours

Crocking (AATCC 165)

≥ 4.0 Wet or Dry

Static Electricity (AATCC-134) 20% R.H., 70° F.

≤ 3.5 KV, Permanent Conductive Fiber

Recommended Maintenance

Daily Vacuum, Deep Clean via Hot Water Extraction

Indoor Air Quality—CRI Green Label Plus™

GLP7205, Carpet Category 13X

Recommended Installation Method(s)

Monolithic, Quarter-Turn, Ashlar

Pieces Per Box

12 Tiles, 32.29 ft² (3.0 m²)

Installation Zone Application

Zone 2 or Zone 3

WARRANTIES

Lifetime Face Fiber Wear

Lifetime Antistatic

Lifetime Floor Compatibility

Lifetime Color Pattern Permanency

Lifetime Floor Release

Lifetime Cushion Resiliency

Lifetime Moisture Resistance

Lifetime Delamination of Backing

Lifetime Staining/Soiling (StainSmart®)

Lifetime Dimensional Stability

Lifetime Tuft Bind

Lifetime Edge Ravel



This cushion-back carpet tile product is covered by one or more patents, published applications and/or patents pending. Specifications are subject to normal manufacturing tolerances and may be changed without prior notice. Copies of actual test results are available upon request.