



## Technical specification | Bahama

Type	: tufted non filled synthetic grass carpet	
Yarn material	: PE monofilament straight & PP monofilament curled	
Yarn type	: 7.200/8 dTex + 3.100/8 dTex	
Yarn quality	: environmental friendly, UV stabilized, UV stability meets DIN 53387 standard : free of lead and cadmium	
Colour fastness	: xenon test: blue scale > 7, grey-scale > 4	
Primary backing	: 100% PP Thiobac ® with fleece, black, UV stabilized : weight 155 gr/m <sup>2</sup>	
Secondary backing	: black latex compound with a base of styrene-butadiene (SBR), with drainage holes : weight 850 gr/m <sup>2</sup>	

Tuft gauge	: 3/8"	
Pile height	: 26 mm	(+/-10%)
Stitches per 10cm	: 15,0	(+/-10%)
Stitches per m <sup>2</sup>	: 15.750	(+/-10%)
Face weight	: 1.000 gr/m <sup>2</sup>	(+/-10%)
Total weight	: 2.005 gr/m <sup>2</sup>	(+/-10%)

Roll width	: 400cm + 200cm	(+/- 2cm)
Roll length	: 25.20 m <sup>1</sup> : roll length may vary	(+/- 20cm)

Water permeability	: 60 liter/min/m <sup>2</sup>
Fire retardant classification	: Cfl-S1 (EN ISO 11925-2: sand filled ca. 5mm) : Efl-S1 (EN ISO 11925-2: non filled)
Batch information	: before installation make sure the first 4 digits of the roll number are equal
Shrinkage	: shrinkage can appear due to high temperatures. Make sure the carpet can relax before cutting
Infill recommendation	: non infill (optional 5kg/m <sup>2</sup> )