

TECHNICAL SHEET

CleanMid[®]B

12, 20 & 25 mm

*The perfect balance between
functionality and aesthetics*



DESCRIPTION



This rollable entrance mat consists of aluminium profiles containing inserts and are compatible with continuous brush or scraping profiles. The CleanMid is highly modular thanks to its unique composition. Flexible PVC strips on the bottom connect the profiles to one another. At regular intervals, the PVC strips are perforated to evacuate the dirt. They also have a sound absorbing and anti-slip function.

Depending on the chosen inserts and the possible combinations with continuous brush or scraping profiles, the function of the entrance mat is to scrape, dry or a combination of both. This mat offers a solution to each problem. The open structure ensures a better absorption of dirt and moisture and makes it easier to roll up the mat. Another asset is the large colour palette of dry and scrub inserts.



MAT CHARACTERISTICS

The total height of the mat is 12, 20 or 25 mm. A flexible PVC strip connects the aluminium profiles. The distance between the profiles is max. 4 mm. The CleanMid Light with dry/scrub, rubber or triplebrush inserts weighs respectively approximately 11, 14 or 15 kg/m². In combination with a continuous brush, the weight is respectively 16 and 17 kg/m² for the heights 20 or 25 mm.

MATERIAL CHARACTERISTICS

Profiles	
Material	aluminium (min 78% recycled)
Sizes	32 mm width & 10, 18 or 22 mm height
PVC connection strips	
Black hard PVC	black crack resistant GST66901 PE LD
Accessories	
Socket screws	stainless steel DIN 916A2 M4x8 aluminium end caps
Screws	stainless steel DIN 7982 A2 C2, 9x13 H
Scraping profile	
Material	aluminium
Brushes	
Material	
Height brushes	

Inserts	
Height textile	5 mm
Width textile	30 mm
Width textile base	29,5 mm
Material dry insert	dry 100% multifilaments polyamide 6 Ø 50.450.000 multifilaments per m ² Colours : anthracite, black, brown, red, grey, green • Full colour scheme: see website. 80% of regenerated textile
Material scrub insert	scrub 99% multifilaments polyamide 6 > 50.450.000 multifilaments per m ² 1% monofilaments polypropylene Ø 500.000 multifilaments per m ² 80% of regenerated textile
Material rubber insert	shrink-free EPDM shore hardness 80 to 90
Material triplebrush insert	PVC and brushes

TESTS

In collaboration with Ghent University

Fire test	The mat is conform to class Bfl in the walking direction, in accordance with EN ISO 11925-2 and EN ISO 9239-1.
Smoke test	The mat is conform to class S1 for dry/scrub and class S2 for triplebrush (2012).
Light fastness test (resistance to photo-degradation)	This test is carried out in accordance with ISO 105 B02 (1994) and gives as result class 6-7. Class 8 is the best result (2002).
Wronz test (heavy wear test)	The mat achieves a value of 25.000, being the equivalent of 500.000 to 1.200.000 steps. See testing reports 02-796C, 02-797C and 02-798C.
Static load test	The mat withstands a pressure of 400 kg per cm ² for the version in 12 mm and 600 kg per cm ² for the version in 20 and 25 mm. See testing reports 03-601 and 03-601 bis. There is no restriction for the load created by normal passages, shopping carts and wheelchairs. For heavy traffic, Verimpex recommends to always use a security plate and to avoid all circular movements.
Moisture absorption test	The capacity of the mat to absorb moisture is above 1000 ml/m ² for dry/scrub and almost 800 ml/m ² for the combination with uninterrupted brushes. See testing reports 02-796B, 02-797B and 02-798B.

Fire and smoke tests have been performed following the classification EN13501-1 (2007+A1:2009). The products are neither impregnated nor coated; it always concerns sustainable characteristics of the used materials.