



**Product:** Monotone

**Customs tariff number:** 57032999

Product details: » Complementary plain colours

- » Dust, dirt and moisture control » Extremely durable nylon surface
- » 15 % recycled rubber » Skid resistant rubber back
- » Light- and colour resistant
- » PVC-free
- » Suitable for underfloor heating
- » 5 year Manufacturers Guarantee\*
- » 11 year warranty against significant colour loss
- » Made in Europe

NFSI High-Traction

EN 13501-1 / Cfl-s1 **Burning behaviour:** 

Total mat weight: 2.40 kg/sqm

Overall height: approx. 11 - 12 mm

Dirt absorption: 800 g/sqm Moisture absorption: 3 - 4 l/sqm

» Busy public entrances **Application areas:** 

» Business receptions

» Hallways

» Elevators

» Restrooms

Standard widths with borders: 85 cm, 115 cm and 150 cm

Standard widths without borders:

Standard lengths:

**Colouration:** Solution dyed

100 % High-Twist Nylon (HTN) Polyamide 6 Pile: Pile height: approx. 10 - 11 mm

(e.g. 82 cm)

all lengths up to 700 cm

Pile weight: without substrate: 600 g/sqm with substrate: 700 g/sqm

Backing: 100 % Nitrile rubber

(15 % recycled nitrile rubber)

Available with kleeted or smooth backing

3 cm smaller than for mats with borders

**Rubber thickness:** 1.40 mm Rubber weight: 1.70 kg/sqm Border width: 20 mm

Available with or without borders **Border thickness:** 

2.40 mm

Cleaning: » Washable up to 60 °C

(Washing is not recommended for mats without reinforced edges when rubber backing is less than 1.8 mm thick)

» Tumble dry up to 60 °C

## Colours:



Slip resistance:



















