


## Colours



**Anthracite**  
007  
NCS: 8500N



**Brown**  
014  
NCS: 8502R



**Red**  
016  
NCS: 3560R

## Specifications


### PVC

### PURA<sup>®</sup> BACKING

Pile material	100% Polyamide	100% Polyamide
Pile weight ISO 8543	± 600 gram/m <sup>2</sup>	± 600 gram/m <sup>2</sup>
Use classification EN 1307	33	33
Flammability Euroclass EN 13501	Cfl /s1	Cfl /s1
Sizes rolls ***	100/200 cm, ± 20 m <sup>1</sup>	100/200 cm, ± 20 m <sup>1</sup>
Sizes mats***	60/90, 90/150 cm	60/90, 90/150 cm
Backing	PVC	<b>PU</b>
Sand absorption class*	2	2
Optical Class**	NPD	NPD
Absorption capacity TNO W6034	± 3,8 l/m <sup>2</sup>	± 3,8 l/m <sup>2</sup>
Total weight ISO 8543	± 3.000 g/m <sup>2</sup>	<b>± 2.700 g/m<sup>2</sup></b>
Pile height ISO 1766	± 6,5 mm	± 6,5 mm
Total height ISO 1765	± 8,0 mm	± 8,0 mm
Pile density ISO 8543	0,079 g/cm <sup>2</sup>	0,079 g/cm <sup>2</sup>
Number of stitches ISO 1763	± 64.500 /m <sup>2</sup>	± 64.500 /m <sup>2</sup>
Wearing class EN 1963	33	33
Comfort EN 1307	LC1	LC1
Dimensional stability ISO 2551	<0,4%	<0,4%
Light fastness ISO 105 B02	>7	>7
Water fastness ISO 105 B01	4 – 5	4 – 5
Rubbing fastness ISO 105 X12	4 – 5	4 – 5
Salt water ISO 105 E02	4 – 5	4 – 5
Shampoo BS 1006	4 – 5	4 – 5
Organic solvents ISO 105 X05	4 – 5	4 – 5
Static charge ISO 6356	<0,1 kV	<0,1 kV
Slip Resistance EN 13893	DS	DS
Yarn construction	Bouclé	Bouclé
Design	Blended	Blended
Colours	3	3
Suitability for stairs EN 1963	Intensive use	Intensive use
Suitability for castor chairs EN 985	Intensive use	Intensive use
Primary backing	nonwoven PET/PA	nonwoven PET/PA
Declaration of Performance	Available	Available

Excluding loose-laid mats  
EN 18641:2008

\* Sand Absorption Class 3: ≥90%, Sand Absorption Class 2: 80% ≤ class 2 < 90%, Sand Absorption Class 1: ≤80% \*\* Optical Class: 5 is best, 1 is lowest \*\*\* All listed dimensions include a PVC edge of 2.5 cm. The roll lengths are an indication. Delivered length can be up to 15% higher or lower. Installation and maintenance advice is available on our website.



## PURA<sup>®</sup> BACKING

Pura Backing™ makes walk-off entrance mats more sustainable by avoiding the use of PVC and plasticisers. It's the response to increasing demand by commercial and residential decorators for environmental sensitivity and sustainability, down to the last details – even when it comes to entrance mats. Mats with Pura Backing™ meet this requirement – with zero PVC and plasticiser content and a smaller environmental footprint, while being even easier to install!

## Contact us for more information

Our employees are ready to answer questions or to take your orders. **Call +31 38 385 35 00** or **mail customerservice@rinos.com**

## Where to use?

	high traffic	medium traffic
Not combined with outdoor matting (scraping)	A	B
Combined with outdoor matting (absorbing)	C	D
Outdoor matting	E	

© Rinos B.V.